DELL EQUALLOGIC" PS5500E

The Dell EqualLogic PS5500E is a virtualized iSCSI SAN that combines intelligence and automation with fault tolerance to provide simplified administration, rapid deployment, enterprise performance and reliability, and seamless scalability. The PS5500E delivers the lowest cost-per-gigabyte in the EqualLogic family with up to 48 TB of SATA storage in a high-density 4U chassis. A PS Series SAN built with PS5500E arrays can scale up to 576 TB under a single, intuitive management interface.

EXCEPTIONAL EASE OF USE

The PS5500E is an intelligent storage array that is designed to provide rapid deployment, simple management and seamless expansion. All PS Series storage arrays include SAN configuration features and capabilities that sense network topology, automatically build RAID sets, and conduct system health checks to help ensure that the array is fully functional out of the box. The EqualLogic PS5500E is designed to be cabled, configured, and serving storage in less than one hour.

MODULAR DESIGN WITH ENTERPRISE RELIABILITY

EqualLogic PS Series arrays are based on a virtualized modular storage architecture that enables IT managers to purchase only the storage they need, when they need it — preventing both underutilization and over-provisioning. Using innovative data movement technology, all EqualLogic PS Series arrays in a SAN work together to automatically manage data, load balance across all resources, and expand to meet growing storage needs.

The Dell EqualLogic PS Series is designed to meet and exceed the rugged requirements of today's data center. The PS5500E includes fault tolerance capabilities through fully redundant and hot-swappable components — dual-controllers, triple fan trays and power supplies, and disk drives with hot spares.

ENTERPRISE DATA SERVICES WITHOUT ADDITIONAL COST

The PS5500E has built-in storage features once relegated to top-tier data centers, enabling best practice storage for every size organization. The EqualLogic PS Series arrays include the following enterprise data services and software features with no additional software licensing fees:

MANAGEMENT | PS Group Manager • Rapid Provisioning • Remote Setup Wizard • Roles-Based Administration • Volume Management

DATA PROTECTION, AVAILABILITY AND RECOVERY | Auto-Replication, Multi-Way • Instant Volume Restore • Multi-Path I/O' • Multi-Volume, Writeable Snapshots • Snapshot and Auto-Replication Scheduler • Volume Cloning • Volume Consistency Sets

STORAGE VIRTUALIZATION | Array Evacuation • Automatic Load Balancing • Automatic or Manual Storage Tiering • Complete SAN Virtualization • Online Data and Volume Movement • RAID Load Balancing • Storage Pools • Thin Provisioning

MAINTENANCE | Auto-Stat Disk Monitoring System • E-mail Home • Enclosure Monitoring System • Performance Monitoring

SERVER MANAGEMENT AND PROTECTION INTEGRATION | Auto-Snapshot Manager/Microsoft Edition² • Auto-Snapshot Manager/VMware Edition³ • Automatic MPIO Connection Management • Microsoft VSS and VDS Providers • Smart Copy for Microsoft® Exchange®, SQL Server®, Windows® File Systems and VMware® VMFS • VMware® Site Recovery Manager Adapter

FLEXIBILITY WITH LOW COST OF OWNERSHIP

The Dell EqualLogic PS Series arrays represent a breakthrough in storage economics, from purchase and setup to operation and upgrades. Unlike traditional SANs, the EqualLogic PS Series comes complete with the available software and applications expected from an enterprise-level SAN. The PS Series scales on-demand — and online — allowing storage growth without disrupting applications. As a result, EqualLogic PS5500E arrays provide exceptional flexibility at a low total cost of ownership.

Whether consolidating a direct-attached storage (DAS) infrastructure, migrating data from an existing SAN or NAS system, streamlining data protection processes, or simply adding storage capacity, the EqualLogic PS Series from Dell offers a family of proven, high-performance, self-managing storage arrays designed to meet the requirements of today's critical datacenter environments.

¹Qualified for Microsoft Windows Server 2000 and 2003, VMware[®], Linux[®] and Sun[™] Solaris[™] Operating Systems ²Qualified for Microsoft Windows Server[®] 2003 and Windows Server[®] 2008 ³Qualified for VMware[®] ESX 3.5, ESXi 3.5 and ESX 3



FEATURES	DELL EQUALLOGIC™ PS5500E
Product Configurations	
Storage Controllers	Dual controllers with a total of 4 GB battery-backed memory Battery-backed memory provides up to 72 hours of data protection
Hard Disk Drives	Forty eight (48) SATA hot-pluggable hard disk drives
Drive Capacities	7,200 RPM SATA II drives available in 500 GB or 1 TB
System Capacities	24 TB using forty eight (48) 500 GB SATA disk drives 48 TB using forty eight (48) 1 TB SATA disk drives
Technical Highlights	
Volumes	Up to 1,024
Snapshots	512 per volume / up to 10,000 total
Hosts Accessing PS Series Group	Up to 512 per pool / 2,048 per group
Host Protocol	Any standards-compliant iSCSI initiator
Operating Systems Supported	Windows [®] 2000 Server, Windows Server [®] 2003, Windows Server [®] 2008, including Hyper-V [®] , Windows Vista [®] , Windows XP [®] , Red Hat [®] Enterprise Linux [®] , SUSE [®] Linux Enterprise, Linux, Sun [®] Solaris, UNIX [®] , IBM [®] AIX [®] , HP-UX, Mac OS [®] X, VMware [®] ESX Server 3 / 3.5 / ESXi 3.5, Citrix XenServer, Virtual Iron [®] , Novell [®] Netware [®]
RAID Support	RAID 50
GbE Network Interfaces	Three (3) copper per controller
TCP Network Support	IPv4, IPv6 core support including JITC
Expansion Option	Can be combined with other EqualLogic PS Series online in the same SAN group; PS5500E can only be in a pool with other PS5500E systems
Reliability	Redundant, hot-swappable controllers, power supplies, cooling fans and disks Individual disk drive slot power control
Enclosure Monitoring System	Automatic spare configuration and utilization SMART Automatic bad block replacement Auto-Stat Disk Monitoring System (ADMS) to monitor health of data on disk drives
Management Interfaces	SNMP, telnet, SSH, HTTP, Web (SSL), host scripting Serial console Multi-administrator support Ability to configure a separate management network
Security	CHAP authentication Access control for iSCSI Access control for management interfaces including RADIUS support
Notification Methods	SNMP traps, e-mail, syslog
Power	AC voltage: 100-240 VAC ±10% single phase Frequency: 47-63 Hz Power factor: 0.95 (minimum) Power consumption: 1400 VA, 1,400 PeakVA (operating maximum) Heat dissipation: 3,400 BTU per hour (maximum) Power supplies: Three 440W dc
Environmental	Temperature range: 5 to 35°C / 41 to 95°F Storage temperature: -20 to 60°C / -22 to 140°F Altitude: -70 to 3,000 m operational / -305 to 12,192 m non-operational Relative humidity: 20 to 80% non-condensing operational / 5 to 95% non-condensing non-operational Shock: 5 g 10 ms ½ sine operational / 30 g 10 ms ½ sine non-operational Vibration: Random .21 grms @ 5-500Hz operational / Random 1.04 grms 2-200Hz non-operational Acoustics: LwA 6.6 Bels Air Quality: Airborne contaminant level of G2 or lower as defined by ISA-S71.04-1985
Physical	Height: 17.5 cm / 6.89 in / 4 EIA units Width: 48.3 cm / 19.01 in / 1EC Rack Compliant Depth: 81 cm / 31.9 in Weight: 74.8 kg / 165 lb
Customer Care Services Programs	Dell EqualLogic PS5500E Customer Care Plus: 24-hour priority online/telephone access, software maintenance and updates, 4-hour onsite advance hardware replacement Dell EqualLogic PS5500E Customer Care: 24-hour priority online/telephone access, software maintenance and updates, next business day advance hardware replacement Limited Warranty: 2 years telephone support (business hours 9AM-5PM EDT/EST USA); 1 year software maintenance and updates; 2 years hardware (return to factory, first 90 days advance replacement, pass through of drive manufacturer warranty)
Additional Services	Dell Services can architect, deploy and optimize an IT environment for your business ensuring that the data you need is available to keep your business running and secure [*] Keep Your Hard Drive: Available for customers who want to retain control over sensitive data.



Dell Inc. 300 Innovative Way Nashua, NH 03062 USA

Telephone: 603-579-9762 Facsimile: 603-579-6910 Toll Free USA and Canada: 888-579-9762

Dell is a trademark of Dell Inc. C 2008 Dell Inc. All rights reserved. SS636_USA_072908