

EMC DATA DOMAIN DEDUPLICATION STORAGE SYSTEMS



EMC Data Domain deduplication storage systems continue to revolutionize disk backup, archiving, and disaster recovery with high-speed, inline deduplication. By consolidating backup and archive data on a Data Domain system, you can reduce storage requirements by 10-30x, making disk cost-effective for onsite retention and highly efficient for network-based replication to disaster recovery sites.

Data Domain Systems

Specifications

DATA DOMAIN CONTROLLER PERFORMANCE AND CAPACITY

	DD160	DD620	DD640	DD670	DD860	DD890	DD990
Maximum Throughput (Other)	667 GB/hr	1.1 TB/hr	2.3 TB/hr	3.6 TB/hr	5.1 TB/hr	8.1 TB/hr	15.0 TB/hr
Maximum Throughput (DD Boost)	1.1 TB/hr	2.4 TB/hr	3.4 TB/hr	5.4 TB/hr	9.8 TB/hr	14.7 TB/hr	31.0 TB/hr
Logical Capacity¹	40 – 195 TB	83 – 415 TB	0.32 – 1.6 PB	0.6 – 2.7 PB	1.4 – 7.1PB	2.9 – 14.2 PB	5.7 – 28.5PB
Logical Capacity w/ DD Extended Retention	-	-	-	-	5.7 – 28.5 PB	-	20 – 100 PB
Max ES30 Shelves Supported (1TB HDD)	-	-	2	4	12	16	24
Max ES30 Shelves Supported (2TB HDD)	-	-	1	2	6	12	24
Max ES30 Shelves Supported (3TB HDD)	-	-	-	-	-	-	16
Max ES30 Shelves Supported (2TB HDD) w/ DD Extended Retention	-	-	-	-	24	-	56
Max ES30 Shelves Supported (3TB HDD) w/ DD Extended Retention	-	-	-	-	-	-	56

1. Mix of typical enterprise backup data (file systems, databases, email, developer files). The low end of capacity range represents a full backup weekly or monthly, incremental backup daily or weekly, to system capacity. The top end of the range represents full backup daily, to system capacity. All capacity values are calculated using Base10 (i.e., 1TB = 1,000,000,000,000 bytes).

DATA DOMAIN CONTROLLER PHYSICAL SPECIFICATIONS AND ENVIRONMENTALS

	DD160	DD620	DD640	DD670	DD860	DD890	DD990
Weight	7 HDDs: 49lbs 12 HDDs: 57lbs		7 HDDs: 51lbs 12 HDDs: 58lbs	66lbs	52lbs		110lbs
Dimensions	19" x 22" x 3.5" 2U EIA rack units			19" x 29.5" x 3.5" 2U EIA rack units			16.7" x 27.7" x 6.8" 4U EIA rack units
Power 100-120/200-240 V ~, 50/60 Hz	7 HDDs: 330 VA 12 HDDs: 373 VA		7 HDDs: 451 VA 12 HDDs: 526 VA	724 VA	640 VA	580 VA	1,400 VA
Thermal Rating (Watts)	7 HDDs: 331 Watts 12 HDDs: 339 Watts		7 HDDs: 428 12HDDs: 500	688 Watts	608 Watts	551 Watts	1,400 Watts
Thermal Rating (BTU/hr)	7 HDDs: 1,061 BTU/hr 12 HDDs: 1,157 BTU/hr		7 HDDs: 1,462 12HDDs: 1,705	2,347 BTU/hr	2,075 BTU/hr	1,881 BTU/hr	6,924 BTU/hr
Operating Temperature/Altitude²	10°C to 35°C, 35°C at 7,500 ft		5°C to 35°C, 35°C at 7,500 ft				
Non-Operating (Transportation) Temperature	-40°C to +65°C (-40°F to +149°F)						
Operating Humidity	20% to 80% non-condensing						
Operation Acoustic Noise (Sound Power)	LWAd: 7.0 bels		LWAd: 7.52 bels	LWAd: 7.4 bels	LWAd: 7.52 bels		LWAd: 7.52 bels
Operation Acoustic Noise (Sound Pressure)	-		LpAm: 56.4 db	LpAm: 58 db	LpAm: 56.4 db		LpAm: 56.4 db

² Derate 1.1°C/1,000 ft above 7,500 ft to 10,000 ft

DATA DOMAIN CONTROLLER REGULATORY APPROVALS

	DD160	DD620	DD640	DD670	DD860	DD890	DD990
Safety	UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1, GS, SABS, GOST, IRAM						
Emissions	FCC Class A, EN 55022, CISPR 22, VCCI, BSMI, MIC, ICES-003						
Immunity	EN 55024, CISPR 24						
Power Line Harmonics	EN 61000-3-2						

SOFTWARE

SOFTWARE FEATURES

Global Compression™, Data Invulnerability Architecture including inline verification and integrated dual disk parity RAID 6, snapshots, telnet, FTP, SSH, email alerts, scheduled capacity reclamation, Ethernet failover and aggregation, Link Aggregation Control Protocol (LACP), VLAN tagging, IP aliasing, EMC Data Domain Boost, EMC Data Domain Encryption, EMC Data Domain Extended Retention (DD860 and DD990 only, cannot be used in conjunction with EMC Data Domain Encryption), EMC Data Domain Replicator, EMC Data Domain Retention Lock optional software and EMC Data Domain Virtual Tape Library (for open systems and IBM i operating environments)

SYSTEM MANAGEMENT

EMC Data Domain System Manager, EMC Data Domain Management Center, SNMP, and command line management interface

DATA MANAGEMENT

NFS v3 over TCP, CIFS and DD Boost over 1 GbE or 10 GbE, tape library emulation (VTL) over Fibre Channel, and NDMP Tape Server

DATA DOMAIN RACK

POWER CONFIGURATION

Single phase is standard, optional 3-phase

Two power domains (base and extended), each redundant

POWER INLET COUNT

Either two (for redundant base configuration) or four (for redundant extended configuration)

PLUG TYPES

NEMA L6-30p or IEC 60309 332P6

POWER CAPACITY

200-240 V~, single-phase, 47-63 Hz

4,800 VA (base configuration)

9,600 VA (extended configuration)

AC PROTECTION

30 A site circuit breaker on each power domain

DIMENSIONS

40U available rack capacity

Height: 75 in (190.8 cm); Width: 24.0 in (61.1 cm); Depth: 39.0 in (99.2 cm)

Weight: 380 lbs (173 kg) when empty

ES30 EXPANSION SHELF

EXTERNAL INTERFACE (HOST/EXPANSION)

Dual 4 lane 6 Gb/s serial attached SCSI II (SAS) ports per Link Control Card (LCC)—one for host and one for expansion

CONNECTOR TYPE

SFF-8088 connectors (mini-SAS)

SAS CABLE LENGTH

Up to 5 meter

DISK DRIVES

15-drive bays per ES30 expansion shelf, support low profile, one inch high, 3.5-inch form factor drives

Drives Choices

- SATA I (3 Gb/s) 3TB, 7200 RPM*
- SATA I (3 Gb/s) 2 TB, 7200 RPM
- SATA I (3 Gb/s) 1 TB, 7200 RPM
- Integrated SAS expander module
- Point-to-point disk connectivity

* ES30 expansion shelf with 3 TB drives is only available for the Data Domain DD990

DIMENSIONS

Height: 5.25 in (13.34 cm)

Width: 19.0 in (48.3 cm)

Depth: 14.0 in (35.56 cm)

Weight: 68 lbs (30.8 kg)

OPERATIONAL

Power (VA): 100-120/200-240 V~, 50/60 HZ 280 VA

Thermal Rating: 800 BTU/hr, 235 Watts

Operating Temperature/Altitude: 10°C to 35°C (50°F to 95°F)

Operating Humidity: 20% to 80%, non-condensing

Non-Operating (Transportation) Temperature: -40°C to +65°C (-40°F to +149°F)

Operating Acoustic Noise Declared noise emission values per ISO 9296:

Sound Power, LWAd: 6.5 bels

Sound Pressure, LpAm: 48.5 dB

EMC², EMC, the EMC logo, are registered trademarks or trademarks of EMC Corporation in the United States and other countries. VMware are registered trademarks or trademarks of VMware, Inc., in the United States and other jurisdictions. © Copyright 2013 EMC Corporation. All rights reserved. Published in the USA. 4/13 Specification Sheet H11340.1

EMC believes the information in this document is accurate as of its publication date. The information is subject to change without notice.

CONTACT US

To learn more about how EMC products, services, and solutions can help solve your business and IT challenges, contact your local representative or authorized reseller—or visit us at www.EMC.com.

www.EMC.com

EMC²
®