

IBM @server® 326m



Highlights

- Delivers outstanding dual-core price/performance for 32-bit and 64-bit high-performance computing applications
- Enabled with IBM Xtended

 Design Architecture[™] features
 for robust performance
- Features integrated System Management Processor for maximum solution control

Superior performance, affordable price

The IBM @server® 326m packs impressive computing power in a 1U rack-optimized design and is ideal for customers requiring large memory addressability and the need to run multi-threaded applications at an affordable price.

The AMD Opteron™ architecture uses an integrated memory controller and innovative HyperTransport™ technology to provide memory access and substantial I/O bandwidth at the speed of the processor. The e326m delivers high memory bandwidth for large data set applications with exceptional performance.

IBM Xtended Design Architecture

With IBM Xtended Design Architecture, the e326m combines innovation with industry standards to provide customers affordable performance-optimized solutions. Enhancements such as 16GB of maximum memory and faster I/O capability deliver exceptional performance. Availability features such as hot-swap SCSI and integrated RAID-1 provide high data access and increased uptime so customers can run their servers with confidence.

Flexible management options

The e326m comes standard with an integrated IPMI 1.5-compliant System Management Processor to help manage your servers. Standard features such as remote power control, text console redirect over serial or LAN, and unattended install help manage your workloads and maximize uptime. These features and other system capabilities can be supported and managed easily with IBM Director software.

Get it now

e326m at a glance Form factor/height Rack/1U AMD Opteron™ processor 252, 254, 265, 270, 275 and **Processor** 280 Number of processors (std/max) 1/2 Cache (max) 2 x 512MB/16GB PC3200 ECC DDR SDRAM Chipkill™ Memory¹ (std/max) **Expansion slots** 2 PCI-Express or 1 PCI-Express and 1 PCI-X **Disk bays** (total/hot-swap) 2/2 600GB Ultra320 SCSI/320GB SATA Maximum internal storage^{1, 2} **Network interface** Dual integrated Gigabit Ethernet Power supply (std/max) 411W 1/1 SCSI HDDs **Hot-swap components** Integrated RAID-1 standard (SCSI model only) **RAID** support **Systems management** Integrated System Management Processor, Cluster Systems Management, IBM Director, supports optional Remote Supervisor Adapter II **Operating systems supported** Microsoft® Windows® Server 2003, Red Hat Linux®, SUSE LINUX Limited warranty³ 1-year onsite limited warranty

For more information	
World Wide Web	
U.S.	lbm.com/eserver/326m
Canada	lbm.com/pc/ca/eserver/opteron/
	index.shtml
Buy Direct	
U.S.	1 888 SHOP IBM
Canada	1 888 SHOP IBM
Reseller locator and	generation information
U.S.	1 800 426-4968
Canada	1 800 426-2255

- Maximum internal hard disk and memory capacities may require the replacement of any standard hard drives and/or memory and the population of all hard disk bays and memory slots with the largest currently supported drives available.
- When referring to storage capacity, GB = 1,000,000,000 bytes. Accessible capacity is less.
- ³ Visit ibm.com/pc/safecomputing periodically for the latest information on safe and effective computing. Warranty Information: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, N.C. 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services including those designated as ServerProven® or ClusterProven®. Telephone support may be subject to additional charges. For onsite labor, IBM will attempt to diagnose and resolve the problem remotely before sending a technician.



© Copyright IBM Corporation 2005

Produced in the USA October 2005 All Rights Reserved

IBM reserves the right to change specifications or other product information without prior notice. This publication could include technical inaccuracies or typographical errors. References herein to IBM products or services do not imply that IBM intends to make them available in other countries. IBM PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OR CONDITION OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore, this statement may not apply to you.

This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. Consult your local IBM business contact for information on the product or services available in your area.

All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

IBM, the IBM logo, the e-business logo, @server and Chipkill are trademarks or registered trademarks of IBM Corporation in the United States, other countries or both. For a list of additional IBM trademarks go to ibm.com/legal/copytrade.shtml.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States, other countries or both.

AMD and AMD Opteron are trademarks or registered trademarks of Advanced Micro Devices, Inc. in the United States, other countries or both

HyperTransport is a licensed trademark of the HyperTransport Technology Consortium.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product and service names may be trademarks or service marks of others.